

Bezel 402 - 462

NEC P-Series Integrated Touch Screen



TECHNOLOGY DISTRIBUTORS

Bezel 402 - 462 - Custom Integrated Touch

IDT's Bezel 402-462 are custom designed and integrated touch screen interfaces for the NEC Display P-Series. The integrated touch screen turn the high-performance Displays into an efficient and very reliable interactive multi-touch solution.

The custom integrated touch Bezels are equipped with the unique NextWindow 2150 touch technology to ensure its longevity and reliable non-stop operations.

NextWindows optical touch technology is used by leading companies around the world and across a wide range of industries, including telecommunications, tourism, retail, real estate, public information and others.

With its unique integration design and high-end surface finish, the Bezel P-Series represent great functionality and the good looks.



NEC Display Solutions

Highlights

- Custom Design for NEC Displays P402/462
- Easy installation within 10 Steps
- Full IR Remote Control Functionality
- High-end Colour Finish
- Clear glass for maximum image clarity
- NextWindow 2150 Optical Touch Technology
- Accurate touch sensitivity over the entire screen
- Light touch: No pressure required
- Four-point driverless calibration. No drift.

[Detailed Specification - Page 2](#)

Product Name	Order Information	
	Model No.	Colour
Bezel 402	P402-INT	Black (matt standard)
Bezel 462	P462-INT	Black (matt standard)



Bezel 402 - 462

NEC P-Series Integrated Touch Screen



Bezel 402 - 462 - Product Specification

Page 2

Technical Data: Bezel 402 - 462

*Technical Data applies to Custom Touch Bezel 402-462 only, not to the NEC Public Displays [please review NEC datasheet]

Bezel Material: Mild Steel
Dimension: 402: 945 x 576 x 61mm / 462: 1080 x 650 x 67mm
Surface Finish: Black Metallic (Standard)
Construction: Fully welded mild steel frame
Mounting: Direct fixation at NEC P401/461 panel via Bezel rivets/socket-screws

Touch Technology: NextWindow 2150 Optical Imaging
Glass: 5mm tempered glass
Touch Method: Finger, Gloved hand, or any other Pointer
Touch Activation Force: No pressure required
Touch Accuracy: ± 2 mm (for 40" screen) over 90% of the screen
USB reported touch resolution 32767 x 32767
Touch Calibration: Simple four-point Driverless calibration
Touch Durability: Unlimited
Touch Response Time: 9 ms to 22ms depending on configuration, typical response time 14ms
Luminous Transmission: >92% with glass, 100% without glass

Connectivity: USB A-A
Interface: USB 1.1 (full speed), HID compliant, plug-and-play compatible
Power: +3.3V [via USB A]; USB from powered hub enumerates 350 mA
ESD: Per EN 6100-4-2 1995: Level 4. Contact discharge 8 kV
Air discharge 15 kV on USB
EMC: EN55022, EN55024, CISPR22, CISPR24

Environmental Conditions
Operating Temperature / Humidity: 0°C to 50°C; 10% to 90% RH, non-condensating
Storage Temperature / Humidity: -25°C to 85°C; 10% to 90% RH, non-condensating

Operating Systems: Windows 2000, XP, Vista, Windows7
Mac OS X, Linux (Optional)

Authorized Reseller:

Image Design Technology

Unit 2, 33-35 Alleyne Street
Chatswood NSW 2067

Phone 1300 666 099

www.idt.com.au